

The YES Company!!

SUPERCO
SPECIALTY PRODUCTS

REPAIR
Acoustical Ceiling
Repair Patch in a Can

FILLS CRACKS AND
CREVICES IN BOTH CEILING
TILE AND POPCORN STYLE
CEILINGS.

USE AT:
APARTMENT COMPLEXES,
OFFICE BUILDINGS,
SCHOOL, COLLEGE AND
DORM BUILDINGS,
MUNICIPALITIES, ETC.

Product: # 1096

FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.

REPAIR fills in cracks and crevices in all types of ceilings. Simply spray **REPAIR** to fill in the void and wait for it to dry. If colors do not match use one of 2 shades of ceiling sprays (**ACOUSTA**) for perfect match. Ideally can contents should be at room temperature (70°-75°F) and the surface to be coated at a lower temperature. A thick application is hard to form on warmer surfaces (above 80°F) however, after a coating has been allowed to dry and harden on a cool surface it will be stable at temperatures up to 120°F.



**DO NOT USE ON PLASTICS OR
PAINTED SURFACES**

DIRECTIONS FOR USE:

1. Wipe excess dirt and moisture from surface to be sprayed.
2. Shake can well and remove protective cap.
3. Hold can upright about 12 inches from surface with valve opening pointed away from you.
4. Apply a thin first coat.
5. Allow to dry (5 to 10 minutes) then apply again from a distance of 6-10 inches.

2	HEALTH
2	FLAMMABILITY
0	REACTIVITY
	SPECIFIC

INGREDIENTS

DICHLOROMETHANE
PROPANE
ISOBUTANE

CAS NUMBER

75-09-2
74-98-6
75-28-5

Additional Information

REPAIR is often called "Popcorn-in-a-Can" by many of our customers. Although you may not be able to shoot an entire ceiling with one can, you certainly **WOULD NOT** want to pay an outside contractor to haul out a big machine to fix a couple of ugly scrapes on a tenants ceiling. With **REPAIR** you simply fill in the areas where the acoustical material is missing first with a thin coat then a heavier coat and the job is done. If the color doesn't match, no problem, AIS has just what you need. After the patch has dried, color match your job with **ACOUSTA** in one of two special shades designed to match all ceiling colors. **REPAIR** is paintable. Use it before you roll or spray paint to insure a consistent ceiling texture. **REPAIR** is lightweight and won't fall out of crevice while curing. Use instead of mud for filling small holes in flat ceilings before painting for just this reason.