

The YES Company!!

SUPERCO
SPECIALTY PRODUCTS

RTV-BLACK
LOW VOLITILE
GASKET MAKER

- 100% Silicone Rubber
- Stays Permanently Flexible
- Withstands Temps From -60°F to 450°F
- Instantly forms any size or shape of gasket
- Meets or exceeds OEM volatility specifications
- Won't foul engine sensors

Product # 1158

FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.

BLACK GASKET MAKER Adhesive/Sealant will bond, caulk, seal, fasten, insulate, protect and repair many types of materials. Because it is virtually unaffected by weather, temperature extremes, chemicals and aging, it offers unmatched performance even under the most severe operating conditions. This material also seals or replaces a wide range of cork, paper, asbestos, felt and metal gaskets. **BLACK GASKET MAKER** works on flanges, cover plates, hose connections and threaded assemblies.

DIRECTIONS FOR USE:

1. Remove old gaskets, all oil and grease, then dry the surface.
2. Apply fingertip pressure to valve stem and lay a thin, even bead (1/16" to 1/8"), to one mating surface, encircling all bolt holes.
3. Allow bead to "skin" (approx. 15 minutes) before assembling parts.
4. Assemble carefully and do not over-tighten bolts.
5. If tooling is required, complete within 5 minutes. Remove excess sealant immediately with dry paper towel or knife.



USE ON: Sealing Turbo Housings, Exhaust Manifolds & Oxygen Sensors, Oil Pans/Pumps, Thermostat Housing, Water Pumps, Push Rod Covers, Valve/Axle Covers, Transmission Pans, Weatherstripping, Gear Covers, Timing Gear/Cam, Compressors, Shaft Covers, Electrical Control Boxes

1	HEALTH
1	FLAMMABILITY
0	REACTIVITY
	PROTECTION

INGREDIENTS CAS NUMBER

SILICA, AMORPHOUS	7631-86-9
METHYLTRIAACETOXSILANE	4253-34-3
ETHYLTRIAACETOXSILANE	17689-77-9
POLYDIMETHYLSILOXANE	63148-62-9
POLYDIMETHYLSILOXANE, HYDROXY-TERMINATED	70131-67-8

Additional Information

BLACK GASKET MAKER Silicone Adhesive/Sealant is specifically manufactured for the automotive industry and meets or exceeds OEM volatility specifications so it won't foul oxygen sensors. This remarkable product instantly forms any size gasket and stays permanently flexible providing the ultimate in durability and performance. Use **BLACK GASKET MAKER** instead of plumber's putty and eliminate the leaks cause by slightly loose fixtures breaking the seal provided by putty alone. **BLACK GASKET MAKER** is much faster and easier than Teflon tape and will generally provide a much longer lasting seal. Use on; oil pans, water pumps, valve axle covers, weather-stripping, cam shaft covers, thermostat housings, push rod covers, transmission pans, pipe fittings, hose connections, etc. **BLACK GASKET MAKER** comes packaged in a unique charged-piston can that dispenses a consistent bead without the need of a caulking gun. Use **BLACK GASKET MAKER** in any situation where other adhesive/sealants have failed or a replacement gasket is not readily available.

STORAGE INSTRUCTIONS

Leave a small bead of material which will form a sealing "plug" for reuse. To reuse, gently pull out "plug" and begin to use material. If plug breaks leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.

