

# SNUG

## Anti-Seize Compound

NONFLAMMABLE • WATERPROOF

- PREVENTS GALLING, SEIZING, AND GALVANIC ACTION
- STANDS UP TO EXTREME TEMPERATURE AND EXTREME PRESSURE

- #1009 SNUG - A
- #7001 SNUG - BT
- #7107 SNUG - PA Food Grade

**SNUG** Anti-Seize Compound provides protection against rust and corrosion on metals. Ensures easy disconnection of bolts, spark plugs, threaded fittings, bushings, etc. **SNUG** will protect and lubricate metal parts under sustained temperatures up to 2100° F (1150° C).

Authorized by USDA for use in federally inspected meat and poultry plants.

Exceeds Federal Spec. MIL-A-907D

### AREAS OF USE:

Automotive and trucking fleets, motorcycle and marine shops, construction, chemical and food processing, farming industries, etc.

### DIRECTIONS FOR USE:

Be sure surfaces are free of dirt, dust, oil and grease. **Brush-**

**top:** Apply liberally with brush-top making sure to coat all threads and friction surfaces.

**Aerosol:** Shake well before using. Use can at temperatures above 65° F. Hold can upright and spray 8-10 inches from surface. After each use invert can and spray a few short bursts to clear the valve.

**Piston-can:** Remove plastic cap from applicator. Press applicator against threads to activate pressure valve to eject compound. Move applicator around surface to apply compound.



**SNUG A and SNUG BT both contain Aluminum, Copper and Graphite.**

#### BRUSH-TOP

1	HEALTH
0	FLAMMABILITY
1	REACTIVITY
	SPECIFIC

#### AEROSOL

1	HEALTH
3	FLAMMABILITY
1	REACTIVITY
	SPECIFIC

#### PISTON-CAN

1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
	SPECIFIC

#### BRUSH-TOP INGREDIENTS

COPPER COMPOUND

#### CAS NUMBER

7440-50-8

#### AEROSOL INGREDIENTS

ISOPARAFFINIC HYDROCARBON 64741-66-8  
 COPPER COMPOUND 7440-50-8  
 LIQUIFIED PETROLEUM GAS 68476-85-7

#### CAS NUMBER

#### PISTON-CAN INGREDIENTS

PETROLEUM OIL MIXTURE 8002-05-9  
 COLLOIDAL SILICA 7631-86-9  
 MOLYBDENUM 1317-33-5  
 COMPRESSED NITROGEN 7727-37-9  
 ALUMINUM 7429-90-5

#### CAS NUMBER

## Add it ion al I n f o r m a t i o n

This extreme pressure and temperature lubricant and sealant protects metal parts under sustained temperatures up to 2100° F. High quality formula additives prevent galling, seizing, galvanic action, pitting, and thread distortion. One application assures long term protection, even in damp environments or corrosive salt spray conditions. Resists steam and weathering indoors or out. **SNUG** will not wash off, separate or harden. This high protection formula will not fuse to metals and is non-melting. Using **SNUG** will allow tighter, firmer joints that open more easily. These benefits will shorten down time and reduce costly replacement parts. **SNUG** is non-corrosive and inert to both natural and synthetic rubber and will greatly reduce deterioration from rubber to metal contact. **SNUG** will give aluminum high heat resistance and protects stainless steel from pitting. Available in brush-top cans (**SNUG BT**), aerosol cans (**SNUG A**), and our **SNUG PA** "No Mess Applicator" charged-piston can.