

The YES Company!!



SSP-2001
 Floating Lift Station
 Cleaner and Deodorizer

EMULSIFIES AND LIQUEFIES
 GREASE AND SLUDGE

- USE IN LIFT STATIONS, GREASE TRAPS, SEWAGE PITS, SUMPS, ETC.
- USE AT OFFICE BUILDINGS, SCHOOLS, APARTMENT

PRODUCT #5222 BULK

FOR PROFESSIONAL USE ONLY
 CONSULT LABEL AND MSDS BEFORE USING.

SSP-2001
FLOATING LIFT STATION
CLEANER AND DEODORIZER

SSP-2001 emulsifies and degrades raw sewage as it floats into lift station wells. The accumulation of sewage, grease, oils, fatty acids, calcium, and soap scum form deposits on wet well walls. **SSP-2001**, by nature's own power, liquefies and attacks the grease so it flows away. **SSP-2001** leaves a pleasant Eucalyptus Pine scent that effectively controls offensive odors.

Add **SSP-2001** directly to lift station wet wells in its concentrated form for effortless cleaning. Degreasing and cleaning is accomplished by the rise and fall of the water level. As the water level rises and lowers, **SSP-2001** removes the sludge from the sides of the walls, then "seals and contains" offensive odors from the lift station and totally eliminates the offensive job of cleaning lift station grease traps or sumps manually.

SSP-2001 is biodegradable, non-freezing, contains no phosphates, no quaternary compounds, no chlorinated solvents, and is free from alkali and acids and will not inhibit waste digestion when used as directed.

DIRECTIONS FOR USE:

SSP-2001 should be added to wet well until a layer of 8 to 12 inches is floating on the surface. This initial treatment should remain effective for a period of 3 to 6 months, depending on system demands. Add as needed. **FOR LIFT STATION CLEANING AND DEGREASING:** To start, add enough product to get a 5 - 7 inch base on top of the lift station. Add 2 - 3 gallons directly to area on a bi-weekly basis to keep up the level at 5 - 7 inches

HMIS	
2	HEALTH
2	FLAMMABILITY
0	REACTIVITY
	SPECIFIC

INGREDIENTS

PETROLEUM DISTILLATE

CAS#

8052-41-3

Additional Information

Cleaning lift stations, wet wells, sumps, and grease traps is by far one of the most time consuming and offensive jobs. Then add to that, the fact that these areas get dirty and grimy more frequently, in fact, immediately. In today's world of lean maintenance crews who has time (or the desire) to maintain and clean lift stations and wet wells, anyway. **SSP-2001** is the perfect solution. Applied once every three to six months (or as needed), **SSP-2001** effectively cleans your traps, sumps, pits and wells constantly. This remarkable formula utilizes the rise and fall of the water level inside the pit or tank to emulsify grease and sludge while keeping the walls and sides clean. With **SSP-2001** at work you never have to get into your lift station to clean it or scrape-down the sides. Plus, no more complaints of bad odors coming up into elevator cars or out of vents because **SSP-2001** is a floating chemical that locks in any foul odors and leaves a smell of fresh oranges. **SSP-2001** is biodegradable and environmentally safe to meet your highest standards. We at Superco Specialty Products are doing our part as a responsible company to help protect our precious natural resources.