



## SUPER COAT-A

**High Solids Industrial Protective Coating**

- Fast Drying - Sag Free
- Excellent Hide - Interior/Exterior
- Fade and Chip Resistant
- Provides Maximum Rust Protection
  - Outdoor / Indoor Durability
- Use on Bare Metal and Wood Surfaces

### Use On:

- Machinery • Racks • Bins
- Motors • Blowers
- Benches • Structural Steel
- HVAC • Sprinkler systems
- Farm/Industrial equipment

Product # 1415 Gloss Black  
Product # 1413 Gloss White

**FOR PROFESSIONAL USE ONLY**  
CONSULT LABEL AND MSDS BEFORE USING.

HMIS	
1	HEALTH
4	FLAMMABILITY
3	REACTIVITY

### INGREDIENTS

ACETONE	67-64-1
PROPANE	74-98-6
n-BUTANE	106-97-8
BARIUM SULPHATE, natural	7727-43-7
GLYCOL ETHER EP	2807-30-9
METHYL ISOBUTYL KETONE	108-10-1
METHYL PORPYL KETONE	107-87-9
XYLENE (mix)	1330-20-7
PM ACETATE	108-65-6
ISOBUTYL ACETATE	110-19-0

**KEEP OUT OF REACH OF CHILDREN**

**EXTREMELY FLAMMABLE**

# SUPER COAT-A

**High Solids Industrial Protective Coating**

SUPER COAT-A is a High Solid industrial coating with a low solvent, high quality and performance formulation, It has single coat hiding power, that saves time and money. One can covers the equivalent of four (4) economy brand low solids paint. SUPER COAT-A paints were tested best in corrosion



protection against the competition by an independent laboratory. They have outstanding hardness and Durability, and resist abrasion and heat.

### DIRECTIONS:

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C.).

2. Shake can at least one minute after rattle is heard and occasionally during use.

3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm).

Several light coats give a better finish than one heavy coat.

Recoat — For best results recoat within 1 hour or after 48 hours. This time varies with curing temperature, humidity, and film thickness. Test a small hidden area before recoating.

4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.

5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly.

DO NOT incinerate or compact.

Contains: See Material Safety Data Sheet for Ingredient Information.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. Primer Coatings Does Not Exceed 60% VOC or 1.20 MIR.

**SUPERCOAT HIGH SOLIDS COATING**