



**SUPER COAT-A**  
**Professional Grade**  
**Primer Coating**

- Fast Drying - Sag Free
- Excellent Hide - Interior/Exterior
- Sandable, Fade and Chip Resistant
- Provides Maximum Rust Protection
  - Outdoor / Indoor Durability
- Use on Bare Metal and Wood Surfaces

**Use On:**

- Metal
- Machinery
- Racks
- Motors
- Farm / Industrial Equipment
- Wood
- Structural Steel
- Fire Doors
- Tanks
- Aluminum
- Bins
- Piping

**Product # 1431**

**FOR PROFESSIONAL USE ONLY**  
 CONSULT LABEL AND MSDS BEFORE USING.

HMIS	
1	HEALTH
4	FLAMMABILITY
3	REACTIVITY

**INGREDIENTS**

- ACETONE
- PROPANE
- n-BUTANE
- VM&P NAPHTHA
- TITANIUM DIOXIDE
- TOLUENE
- XYLENE (mix)
- ETHYL ALCOHOL
- n-BUTYL ACETATE
- MINERAL SPIRITS
- ISOBUTYL ACETATE

**CAS #**

- 67-64-1
- 74-98-6
- 106-97-8
- 64742-89-8
- 13463-67-7
- 108-88-3
- 1330-20-7
- 64-17-5
- 123-86-4
- 64742-47-8
- 110-19-0

**KEEP OUT OF REACH OF CHILDREN**

**EXTREMELY FLAMMABLE**

**SUPER COAT-A**

**Professional Grade Primer Coating**

Superco's **SUPER COAT-A** Primer is a sag-free primer that provides maximum rust and chemical protection. Super Coat Primer provides superior wear resistance and adhesion, and creates a strong base coat on bare metal and wood. Use with **SUPER COAT-A** High Solids Industrial Coatings.



**DIRECTIONS:**

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. Do not stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly.

**DO NOT** incinerate or compact.

**Contains:** See Material Safety Data Sheet for Ingredient Information.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. Primer Coatings Does Not Exceed 60% VOC or 1.20 MIR.