


The YES Company!!



SUPER LUBE

IMPACT

SUPER IMPACT  
HEAVY LOAD  
GREASE

- Wide range of operating temperatures
- 65 Timken OK Load
- Superior water resistance
- Rust and corrosion inhibitors
- Resistant to most acids, dirt, water, steam, and oxidation.
- Lasts longer than many conventional greases

Product # 7114 (bulk)  
Product # 7019 (tubes)

FOR PROFESSIONAL USE ONLY  
CONSULT LABEL AND MSDS BEFORE USING.

**SUPER-LUBE IMPACT**

**Super Impact Heavy Duty Grease**

**SUPER-LUBE IMPACT** is a multipurpose grease fortified with special additives enabling it to withstand the heavy impact and pounding pressures common to heavy equipment. Our special additive package allows the grease to stay in place and not to spatter or pound out of the bearing or fitting. Most greases manufactured today do not have this antispatter capability.

**Composition:**

**SUPER-LUBE IMPACT** contains extreme pressure additives to provide long life under heavy loads, up to 65,000 PSI/65 lb. Timken load. This grease will withstand temperatures up to 550° F. It has superior water resistance and resists most acids, salt spray, steam, dirt, dust and weather. We have also blended extra rust, corrosion and oxidation inhibitors into **SUPER-LUBE IMPACT**. You now have a grease that not only resists high temperatures and heavy loads, but also provides extra protection of equipment with its superior antispatter capabilities. A true long lasting product that can replace many commercially available greases.



**User Benefits:**

- (1) Lasts longer than many conventional grease--won't pound out.
- (2) Performs at a wide range of operating temperatures up to 550°F.
- (3) Excellent load carrying capability 65 lb. Timken Load.
- (4) Superior water resistance.
- (5) Special rust and corrosion inhibitors.
- (6) Resists most acids, weather, dirt, water, steam and oxidation.

**Typical Specifications:**

Color:	Green
Penetration (ASTM D 217):	245-265mm
*NLGI Grade:	2.5
Dropping Point (ASTM D 556):	+550° F (nonmelt)
Timken OK Load (ASTM D 2509):	65 LB.
Water Resistance:	Excellent
Rust Resistance:	Excellent
Acid Resistance:	Excellent

\*National Lubricating Grease Institute

**CAS NUMBERS:**

Petroleum Distillate 8002059; Rheological Thickener 68953-58-2; N.J.# 800983-5015P.

**HMS RATING:**

Health-1; Flammability-1; Reactivity- 0; Personal Protection-B.

Additional Information

**SUPER LUBE IMPACT** Super Impact Grease is a high performance multipurpose grease specifically designed for high pressure and heavy impact applications. Fortified with special additives, **SUPER LUBE IMPACT** will stay in place under extreme pressure conditions such as; lifts, elevators, cranes, fifth wheel plates, hydraulics, heavy load bearings & wheels, conveyors, marine applications, etc. This advanced formula surpasses all commercial or specialty greases in the ability to withstand weight, heat, water and chemicals. To find out more about this product or other fine quality lubricants contact your local **SUPERCO** sales representative.