

The YES Company!!



TAR-OFF
Jell Degreaser & Tar Remover

USED FOR DISSOLVING AND CLEANING TAR, PITCH, ASPHALT, OIL AND GREASE FROM FLOORS, BRICK, ASPHALT SPREADERS, ROAD MACHINERY, HEATING POTS, MOPS, BROOMS, SHOVELS, ETC.

Product # 5732

FOR PROFESSIONAL USE ONLY
 CONSULT LABEL AND MSDS BEFORE USING.

INGREDIENTS	CAS NUMBER
TOLUENE	108-88-3
KEROSENE	8008-20-6
MINERAL SPIRITS	8030-30-6

1	HEALTH
0	FLAMMABILITY
1	REACTIVITY
1	PROTECTION

TAR-OFF
Jell Degreaser & Tar Remover

TAR-OFF cleans and degreases motors on automobiles, trucks, tractors, airplanes, lawn mowers, boats, etc. Excellent for cleaning and degreasing industrial machinery, lawn and turf equipment, municipal equipment, concrete floors and driveways, boat bilges, vertical surfaces, ceilings and hard to reach areas. Removes tar, asphalt and grease from all types of vehicles, equipment and masonry surfaces such as brick, stone, concrete, etc. It emulsifies tar, asphalt, bitumen and asphalt based plastic cements and mono-form roofing compounds used by roofers.

DIRECTIONS FOR USE:

TAR-OFF may be applied by brush or roller. Spray application by hand pump sprayer or by pressurized tank sprayer.

For Engines: Cover distributor and carburetor air inlet with plastic or aluminum wrap to avoid wetting. Allow to sit for at least 10 minutes and remove with high pressure water spray. Remove plastic or aluminum wrap. Idle engine for 15 minutes immediately after hose-off to assure complete drying.

For Tar, Asphalt, Road Oil, Etc., Removal: Spray **TAR-OFF** on area to be cleaned. Let set at least 10 minutes. Agitate if necessary and hose-off with water.

Additional Information

TAR-OFF Jell Degreaser & Tar Remover is designed and formulated for extremely heavy duty use. Industrial applications involving tar, asphalt, crude oil, bitumen and roof cements require a strong degreaser capable of dissolving and emulsifying these heavy soils. Ideal for all masonry surfaces, **TAR-OFF** will quickly remove grease and oil spots from driveways and shop floors, brick, stone and concrete walkways without the need for high-pressure washers. This powerful formula may be diluted with kerosene or used full strength depending on the users requirements. Contact your local **SUPERCO** representative for more information on **TAR-OFF**.