

The YES Company!!



**PATCH-IT
AQUA**
Underwater Epoxy
Repair Kit

- HARDENS IN MINUTES
- BONDS INSTANTLY WITH SUPERIOR STRENGTH
 - EASY TO USE AND MISTAKE PROOF
 - USE FOR INTERIOR OR EXTERIOR

Product # 7111AQ

FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.

PATCH-IT AQUA

Underwater Epoxy Repair Kit

- REPAIR AND REBUILD ANYTHING MADE OF FIBERGLASS.
- REPAIRS DINGS, HOLES, GOUGES, DECKS AND HULLS, POOLS, HOT TUBS & SPAS, MARINE RECREATIONAL EQUIPMENT, LEAKING GASKETS, GUTTERS & TANKS.
- CONTAINS NO SOLVENTS - HAS NO ODOR - WILL NOT SHRINK OR PULL AWAY.
- HAS 15 MINUTE WORKLIFE & HARDENS IN 20-30 MINUTES.

DIRECTIONS FOR USE:

For best results, clean and roughen bond area prior to application. Cut or twist off desired amount of **PATCH-IT AQUA** and knead it to a uniform color. Apply to surface to be repaired (within 2 minutes of mixing). The mixed epoxy does not exhibit high bond strength at this point but appears to be merely lying on the surface. Force into any cracks or holes to be filled and strike off excess material. For a smooth appearance of the cured compound, hand rub with water or a damp cloth prior to hardening. Remove excess material before hardening begins. Within 20-30 minutes the epoxy will harden and form a tenacious bond. Final cure occurs within 60 minutes.



1	HEALTH
1	FLAMMABILITY
0	REACTIVITY
B	PROTECTION

INGREDIENTS

GLYCIDYL ETHERS OF BISPHENOL A RESINS
EPOXY NOVALAC RESIN
POLYMERIC PHEONIC AMINE

CAS NUMBER

Additional Information

PATCH-IT AQUA is a fast setting, fiberglass-reinforced polymer compound that enables permanent repairs to many surfaces concrete and masonry. It also bonds to metal, wood, glass, and many plastics. Each stick contains pre-measured portions of activator and base throughout - no measuring or mixing tools are necessary. As the epoxy is mixed, the two contrasting colors blend into one color to indicate complete mixing. **PATCH-IT AQUA** epoxy contains a fading blue dye and becomes white after mixing. The consistency of **PATCH-IT AQUA** (like modeling clay) eliminates drips and runs, facilitates adhesion to the substrate, and allows the material to be shaped and formed as needed before curing begins. Once cured, it can be drilled, screwed, filed, carved, sanded or painted. **PATCH-IT AQUA** is suitable for interior or exterior use, is resistant to water, chemicals, and temperature extremes. Contact your local **SUPERCO** representative for a demonstration of the effectiveness and versatility of **PATCH-IT AQUA**.