

#### **INGREDIENTS**

**CAS NUMBER** ISOPARAFFINIC HYDROCARBON 64742-46-7 MINERAL OIL 8042-47-5

DIPRPYLENE GLYCOL MONOMETHYL ETHER 34590-94-8 OCTAMETHYLCYCLOTETRASILOXANE 556-67-2 CARBON DIOXIDE PROPELLANT

# **ENVIRONMENTALLY FRIENDLY**

### NON-CHLORINATED PENETRATING LUBRICANT

**PEN-TECH** Penetrating Lubricant & Demoisturant is the most advanced formula available today. This remarkable product does not contain any chlorinated solvents, no 1,1,1-Trichloroethane, no Trichloroethylene(TCE), no Perchloroethylene, no Methylene Chloride or any other dangerous ingredients. **PEN-TECH** is the ultimate in penetrating lubricants, is non-flammable and nonconductive with a dielectric strength of 39,000 volts. PEN-TECH creates a waterproof film that dries out electrical equipment, inhibits corrosion and prevents electrical discharge. PEN-TECH

protects and creates a non-drying film that guards against atmospheric and mild chemical corrosion.

## **MEETS MILITARY SPECIFICATIONS C-23411** Authorized by USDA for use at Federally inspected meat and poultry plants. **DIRECTIONS FOR USE:**

Spray frozen parts liberally, let set and the penetrating formula goes to work. PEN-TECH cuts through grease, displaces any moisture, penetrates and loosens any rust or corrosion making it easy to separate the parts. Repeat as necessary. For faster assembly, spray nuts, bolts and parts before

For wet ignition systems: Remove distributor cap and spray directly onto contacts to restore system.

For wet breakers and switches: Spray directly onto wet contacts to restore

connection. To assure adequate protection reapply periodically.



#### Add ition al Inf or mation

**PEN-TECH** Penetrating Lubricant & Demoisturant is truly the safety department's best friend. This remarkable formula contains NO TCE (Trichloroethylene), NO Perchloroethylene and **NO** Methylene Chloride. **PEN-TECH** out performs other penetrants and lasts longer than other protectants and demoisturants giving you the protection and performance you need. **PEN-TECH** features a non-flammable formula that is non-conductive to 39,000 volts, the highest in the industry. PEN-**TECH** will break loose rusted parts and make disassembly and reassembly faster and easier. This non-drying protectant will seal out moisture and corrosion adding life to expensive electrical equipment that may be subjected to harsh environments. For more information on our comprehensive line of lubricants or a demonstration of the effectiveness of PEN-TECH contact your local SUPERCO sales representative.