

Shiney Bright – All Metal Polish

Safety Data Sheet

SECTION 1: Product and company identification

Product name : Shiney Bright – All Metal Polish
Use of the substance/mixture : Polish
Product code : 4017 SDS Number: 0670
Company : Superco Specialty Products
25041 Anza Drive
Valencia, CA 91355 - USA
T (661) 775-8877
Emergency number : (661) 775-8877

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Irrit. 2 H315
Eye Dam. 1 H318
Carc. 1A H350

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

GHS08

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : Causes skin irritation
Causes serious eye damage
May cause cancer (Inhalation)
Precautionary statements (GHS-US) : Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wash thoroughly after handling
Wear eye protection, protective clothing, protective gloves
If on skin: Wash with plenty of soap and water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If exposed or concerned: Get medical advice/attention
Immediately call a doctor, a POISON CENTER
Specific treatment (see First aid measures on this label)
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
Store locked up
Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Crystalline Silica	(CAS No) 14808-60-7	15-40	Carc. 1A, H350

Shiney Bright – All Metal Polish

Safety Data Sheet

Name	Product identifier	%	Classification (GHS-US)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS No) 64742-47-8	<=2	Flam. Liq. 4, H227 Asp. Tox. 1, H304
Oxalic Acid	(CAS No) 6153-56-6	1-5	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314
UNDECETH-5	(CAS No) 34398-01-1	1-5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
ammonia, anhydrous	(CAS No) 7664-41-7	0.1-1.5	Flam. Gas 2, H221 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
- First-aid measures after skin contact : Wash skin with plenty of water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- First-aid measures after ingestion : Rinse mouth with water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause cancer.
- Symptoms/injuries after inhalation : None under normal use. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : Gastrointestinal complaints. Diarrhea. Nausea. Vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : All extinguishing media allowed.

5.2. Special hazards arising from the substance or mixture

- Reactivity : Thermal decomposition may produce oxides of carbon and nitrogen.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

- Protective equipment : Protective goggles. Gloves. Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers.
- Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

Shiney Bright – All Metal Polish

Safety Data Sheet

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing.
- Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep container closed when not in use.
- Incompatible products : strong acids.
- Storage area : Meet the legal requirements. Store in a cool area. Store in a dry area.
- Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Crystalline Silica (14808-60-7)

OSHA	OSHA PEL (TWA) (mg/m ³)	0.1
------	-------------------------------------	-----

8.2. Exposure controls

- Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Protective goggles. Protective clothing.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Opaque. Beige. Viscous liquid.
- Odor : Pungent.
- Odor threshold : No data available
- pH : 9 - 10
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : > 200 °F Closed Cup
- Relative evaporation rate (butyl acetate=1) : No data available
- Flammability (solid, gas) : No data available
- Explosion limits : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available
- Vapor pressure : No data available
- Relative density : No data available
- Relative vapor density at 20 °C : No data available
- Specific gravity / density : 1.141 g/ml
- Solubility : Soluble in water.
- Log Pow : No data available
- Log Kow : No data available
- Auto-ignition temperature : No data available

Shiney Bright – All Metal Polish

Safety Data Sheet

Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: 1 - 3 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition may produce oxides of carbon and nitrogen.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ammonia, anhydrous (7664-41-7)	
ATE CLP (gases)	700.000 ppmV/4h
UNDECETH-5 (34398-01-1)	
LD50 oral rat	> 1400 mg/kg
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Literature)
Oxalic Acid (6153-56-6)	
LD50 oral rat	375 mg/kg

Skin corrosion/irritation	: Causes skin irritation. pH: 9 - 10
Serious eye damage/irritation	: Causes serious eye damage. pH: 9 - 10
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).

Crystalline Silica (14808-60-7)	
IARC group	1 - Carcinogenic to Humans

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: None under normal use. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Gastrointestinal complaints. Diarrhea. Nausea. Vomiting.

Shiney Bright – All Metal Polish

Safety Data Sheet

SECTION 12: Ecological information

12.1. Toxicity

UNDECETH-5 (34398-01-1)	
LC50 fish 1	< 10 mg/l
EC50 Daphnia 1	< 10 mg/l
ErC50 (algae)	< 10 mg/l
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
LC50 fish 1	> 100 mg/l (Pisces)
EC50 Daphnia 1	> 100 mg/l (Invertebrata)
Threshold limit algae 1	> 100 mg/l (Algae)

12.2. Persistence and degradability

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.

12.3. Bioaccumulative potential

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Log Pow	6 - 8.2
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT : Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ammonia, anhydrous	CAS No 7664-41-7	0.1-1.5
xylene	CAS No 1330-20-7	0.1-1

ammonia, anhydrous (7664-41-7)

Listed on SARA Section 313 (Specific toxic chemical listings)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb

Shiney Bright – All Metal Polish

Safety Data Sheet

UNDECETH-5 (34398-01-1)

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Gas 2	Flammable gases Category 2
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
H221	Flammable gas
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H331	Toxic if inhaled
H350	May cause cancer

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.