

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 1106
Product name Lice & Bedbug Spray
Effective date 25-Oct-2007
Distributed by Superco Specialty Products
25041 Anza Drive
Valencia, CA 91355
Company phone 661-775-8877
Emergency telephone 800-320-0102
Supersedes date 02-Aug-2007

2. Hazards Identification

Emergency overview Prolonged exposure may cause chronic effects. CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when exposed to heat or flame.

OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

Eyes Health injuries are not known or expected under normal use.

Skin Health injuries are not known or expected under normal use.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target organs Central nervous system.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

Signs and symptoms Narcosis.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Propane	74-98-6	5 - 8
n-Butane	106-97-8	3 - 5
Non hazardous and other components below reportable levels		> 90

4. First Aid Measures

First aid procedures

Eye contact Flush eyes with water as a precaution. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.

Skin contact Immediately take off all contaminated clothing. Wash off with soap and water. Get medical attention if irritation develops or persists.

Inhalation Call a physician if symptoms develop or persist.

Ingestion Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If ingestion of a large amount does occur, seek medical attention.

Notes to physician Symptoms may be delayed.

General advice If you feel unwell, seek medical advice (show the label where possible).

5. Fire Fighting Measures

Flammable properties Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media Large Fires: Water spray, fog or regular foam.

Small Fires: Dry chemical, CO₂, water spray or regular foam.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters**Protective equipment and precautions for firefighters**

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Personal precautions

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away.

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Avoid prolonged exposure.

Storage

Level 1 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep container tightly closed. Keep the container dry. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure limits**ACGIH**

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106 97 8	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment**Eye / face protection**

Not normally needed.

Skin protection

Not normally needed.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General hygiene considerations

When using do not smoke. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties
--

Appearance

Compressed liquefied gas.

Color	White.
Odor	None.
Physical state	Liquid.
Form	Aerosol.
Flammability (HOC)	4.37 kJ/g estimated
Flash back	No
Pressure	65 - 75 psig @70F
Solubility	Partially
Flash point	156 °F (104.4 °C) estimated
Boiling point	181.4 °F (82.8 °C) estimated
Specific gravity	0.9166 estimated
pH	7.07 - 8.07

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	May include oxides of nitrogen.

11. Toxicological Information

Acute effects	Acute LD50: 78942 mg/kg estimated, Rat, Oral Acute LD50: 20400 mg/kg estimated, Rat, Dermal Acute LC50: 160 mg/l/4h estimated, Rat, Inhalation
Sensitization	Not expected to be hazardous by OSHA criteria.
Chronic effects	Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.
Neurological effects	Hazardous by OSHA criteria.
Mutagenicity	Not expected to be hazardous by OSHA criteria.
Reproductive effects	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.
Epidemiology	Not expected to be hazardous by OSHA criteria.
Further Information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicity	LC50 1491 mg/L, Fish, 96.00 Hours, Components of this product have been identified as having potential environmental concerns.
--------------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Consult authorities before disposal. Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156. 306
Packaging non bulk	156. 306
Packaging bulk	None

IMDG

Basic shipping requirements:
 Proper shipping name AEROSOLS, flammable
 Hazard class 2.1
 UN number 1950
 Additional information:
 Packaging exceptions LTD QTY
 Item 5F
 Labels required 2.1
 Transport Category 2

**IATA**

Basic shipping requirements:
 Proper shipping name Aerosols, flammable
 Hazard class 2.1
 UN number 1950
 Additional information:
 Packaging exceptions LTD QTY



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
 CERCLA/SARA Hazardous Substances - Not applicable.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IFCSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information

HMIS® ratings

Health: 1*
 Flammability: 2
 Physical hazard: 0

Prepared by

Regulatory Compliance

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

25-Oct-2007