



Section V: REACTIVITY DATA

PRODUCT NUMBER: 4005

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F
Incompatibility (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards(Acute and Chronic):
INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY CAUSE UNCONSCIOUSNESS. EYES:
STRONG IRRITATION. SKIN: IRRITATION. MAY CAUSE DRYNESS AND DEFATTING.
INGESTION: NAUSEA, VOMITING, INTESTINAL CRAMPING.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR.
EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES. CONSULT PHYSICIAN. SKIN:
WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS CONSULT
PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH
RAG OR USE SOME ABSORBENT CLAY MATERIAL

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE
OR LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE
CONTAINER. WRAP AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR
HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE
BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: USE WITH ADEQUATE VENTILATION.
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
N/A

Work/Hygienic Practices:  
WASH HANDS AFTER USE.