

MATERIAL SAFETY DATA SHEET

NPCA

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

Date Issued 11/8/05

SECTION I

MANUFACTURED FOR:

SUPERCO SPECIALTY PRODUCTS

STREET ADDRESS

25041 ANZA DRIVE

CITY, STATE, AND ZIP CODE

VLAENCIA, CA 91355

INFORMATION TELEPHONE NUMBER

1-661-775-8877

PRODUCT CLASS

ELASTOMERIC CRACK FILLER

MANUFACTURES CODE IDENTIFICATION

7062

TRADE NAME

CON-FIX

SECTION II- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3	LEL	VAPOR PRESSURE
ETHYLENE GLYCOL CAS #- 107-21-1	<4%	100			
STODDARD SOLVENT CAS #- 9003-55-8	<7.5%	100			
Acrylic Latex (water based emulsion polymer) CAS #- 7732-18-5	<5%				
Quartz CAS #- 14808-60-7	<18%		0.05		
Hollow Spheres of alumino silicate CAS #- 68131-74-8	<14%		15		

ADDITIONAL INFORMATION-

Hazardous Materials Identification System (HMIS)

Health

1

Flammability

0

Reactivity

0

Personal Protection

B

SECTION III - PHYSICAL DATA

BOILING RANGE: 212°F - 215°F VAPOR DENSITY HEAVIER LIGHTER, THAN AIREVAPORATION RATE FASTER SLOWER, THAN ETHER PERCENT VOTILE BY VOLUME 25 % WEIGHT PER GALLON BY VOLUME 10.2 LBS

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY - NR

FLASH POINT- Water-based Not Applicable

EXTINGUISHING MEDIA- CO2, FOAM, & DRY CHEMICAL or water spray

UNUSUAL FIRE AND EXPLOSION HAZARDS- Not Applicable

SPECIAL FIRE FIGHTING PROCEDURES- WEAR SELF CONTAINED BREATHING APPARATUS FOR FIGHTING LARGE FIRES INVOLVING CHEMICALS. WATER MAY BE USED TO COOL CLOSED CONTAINERS.

SECTION V – REACTIVITY DATA

STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: NONE

INCOMPATIBILITY (MATERIALS TO AVOID): OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

SECTION VI-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE- ACUTE: SKIN: PROLONGED REPEATED CONTACT MAY CAUSE IRRITATION. EYES: MAY CAUSE SLIGHT IRRITATION. INHALATION: EXCESSIVE BREATHING OF HIGH VAPOR CONCENTRATION CAN CAUSE HEADACHE, DIZZINESS, NAUSEA. INGESTION: MAY CAUSE NAUSEA, VOMITING, HEADACHE AND DIZINESS. CARCINOGENITY: NO

CALIF. PROP. 65* CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ)

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR REPRODUCTIVE HARM.

EMERGENCY FIRST AID PROCEDURE- EYES: FLUSH EYES WITH COPIOUS LARGE AMOUNTS OF WATER FOR AT LEAST A5 MINUTES. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING/SHOES. WASH AFFECTED AREAS WITH MILD SOAP AND WATER. , IF IRRITATION DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION. DO NOT REUSE CLOTHING/SHOES UNTIL THOROUGHLY LAUNDERED. INHALATION: REMOVE FROM EXPOSURE. IF BREATHING IS DIFFICULT ADMINISTER OXIGEN. IF BREATHING HAS STOPPED, ADMINISTER ARTIFICIAL RESPIRATION. KEEP PERSON WARM & QUIET. SEEK MEDICAL ATTENTION IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING- TRANSPORT TO HOSPITAL IMMEDIATELY.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: EVACUATE ALL UNNECESSARY PERSONNEL. DO NOT RE-ENTER AFFECTED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT. VENTILATE AREA. COLLECT IN MOST SAFE MANNER FOR DISPOSAL OR RECLAMATION IN SEALED CONTAINERS.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED.

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES:Nitrile RUBBER SHOULD BE USED.

EYE PROTECTION: SAFETY GLASSES SHOULD BE USED

OTHER PROTECTIVE EQUIPMENT:

SECTION IX – REGULATORY INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL PLACE

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN OR CLOTHING.