

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 452
IDENTITY: DOOM
Revision Date: 01/23/2006
=====

Section I

Manufactured For: SUPERCO SPECIALTY PRODUCTS Telephone Numbers:
Address: 25041 ANZA DRIVE Emergency:
800/255-3924
VALENCIA Information:
State: CA Zip Code:91355 661/775-8877
=====

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 7 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 350F+ Specific Gravity (water=1) 0.89
Vapor Pressure(mm Hg) <5 Melting Point: N/A
Vapor Density(AIR=1) 4 Evaporation Rate: <1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: BROWN COLORED SPRAY, PETROLEUM ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used):142F TCC Flammable Limits: LEL:1.0 UEL: 6.0
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS
Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS

Section V: REACTIVITY DATA
=====

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatability (Materials to Avoid): SOME PLASTICS
Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY
PRODUCE CARBON MONOXIDE.
Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

=====
Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards(Acute and Chronic):

INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY LEAD TO UNCONSCIOUSNESS.
INGESTION: NAUSEA. SKIN: IRRITATION AND REDDENING. EYES: IRRITATION AND REDDENING.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL AGGRAVATE RESPIRATORY.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF INDICATED. INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. EYES: FLUSH WITH WATER FOR 15 MINUTES AND CALL PHYSICIAN. SKIN: WASH WITH SOAP AND WATER.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====
Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Precautions to be Taken in Handling and Storing: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE EMPTY CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Other Precautions: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

=====
Respiratory Protection: USE ONLY IN WELL VENTILATED AREAS.

Ventilation: Local Exhaust:ADEQUATE

Mechanical: N/A Special: N/A

Other: N/A

Protective Gloves:RECOMMENDED

Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USE.

Other Protective Clothing or Equipment: N/A

Work/Hygienic Practices: WASH HANDS AFTER USE.