

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 1144
IDENTITY: EASY SLIDE

Revision Date: 01/18/2007

Section I

Manufactured For:	SUPERCO SPECIALTY PRODUCTS	Telephone Numbers:
Address:	25041 ANZA DRIVE	Emergency:
		800/255-3924
	VALENCIA	Information:
	State: CA Zip Code:91355	661-775-8877

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A
Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER	LIM %
ACETONE	67-64-1	1000 PPM	750 PPM	N/A	---
HEPTANE	142-82-5	400 PPM	400 PPM	N/A	---
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	---

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	<200 F	Specific Gravity (water=1)	0.76
Vapor Pressure(mm Hg)	36	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	>1
Solubility in Water:	0%	(Butyl Acetate=1)	

Appearance and Odor: CLEAR SPRAY, SLIGHT SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used):	<5 F TCC	Flammable Limits:	LEL:1.3 UEL: 10.2
---------------------------	----------	-------------------	-------------------

Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS
Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 538

=====
Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120F, HOT SURFACES
Incompatibility (Materials to Avoid): STRONG OXIDIZERS
Hazardous Decomposition or Byproducts: SILICON DIOXIDE, FORMALDEHYDE, CARBON OXIDES.
Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid:

Section VI: HEALTH HAZARD DATA

=====
Routes of Entry: Inhalation: YES Skin: YES Ingestion:NO
Health Hazards(Acute and Chronic):
INHALATION: DIZZINESS. PROLNGED EXPOSURE MAY LEAD TO UNCONSCIOUSNESS. EYES:
MILD IRRITATION. SKIN: MAY CAUSE MILD IRRITATION OR LOCALIZED DEFATTING OF SKIN.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS
Medical Conditions Generally Aggravated by Exposure: NONE KNOWN
Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. SEEK PHYSICIAN IF
BREATHING TROUBLE PERSISTS. EYES: FLUSH WITH WATER FOR 15 MINUTES. SEEK PHYSICIAN
IF IRRITATION PERSISTS. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. SEEK
PHYSICIAN IF IRRITAION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====
Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE ABSORBENT CLAY
MATERIAL.
Waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL
GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE CONTAINER.
WRAP CONTAINER AND PLACE IN TRASH COLLECTION.
Precautions to be Taken in Handling and Storing: DO NOT STORE OR USE NEAR HEAT OR OPEN FLAME.
EXPOSURE TO TEMPERATURES ABOVE 120F MAY CAUSE BURSTING.
Other Precautions: MAY ACCUMULATE AND CREATE A FLAMMABLE ATMOSPHERE
Section VIII: CONTROL MEASURES

=====
Respiratory Protection: N/A
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment: N/A
Work/Hygienic Practices:
WASH HANDS THOROUGHLY AFTER USE.