


MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ELECTRO-TAPE LIQUID
PRODUCT # : 5058

1. Chemical Product and Company Identification

Manufactured for: Superco Specialty Products
25041 Anza Drive
Valencia, CA 91355

Phone Number: 661-775-8877
Emergency Phone: 800-424-9300
Revision Date: 7/11/2005



2. Composition and Information on Ingredients

Ingredient	CAS Number	Weight %	ACGIH TLV	PEL	STEL
Xylene	1330-20-7	41%	100 ppm	100 ppm	150 ppm
Methyl Ethyl Ketone (MEK)	78-93-3	35%			

3. Hazard Identification

Primary Routes of entry: Ingestion, inhalation, and skin contact
Eye Contact: Can cause irritation
Skin Contact: Prolonged or repeated exposure may cause irritation
Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea
Inhalation: May cause respiratory tract irritation. May cause headache and nausea.

Existing Conditions Aggravated by Exposure: Sinus and dermatitis

4. First Aid Information

Eye Contact: Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation develops.
Skin Contact: Wash with soap and water. If irritation occurs, seek medical attention.
Ingestion: DO NOT INDUCE VOMITING. Immediately drink two glasses of water. Never give anything to an unconscious person. Get medical attention.
Inhalation: Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

5. Fire Fighting Measures

Flash Point: 190°F
LEL: 1.2
UEL: 6.6

Extinguishing Media: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

Special Fire Fighting Procedures:

Water may be used to cool closed containers to prevent pressure build-up and possible explosion when exposed to extreme heat. Wear a full face positive pressure self-contained breathing apparatus when fighting fires. Fight like a fuel oil fire. Cool fire exposed containers with water spray. Use water to keep fire exposed containers cool to prevent pressure build-up. Fire fighter should wear OSHA/NIOSH approved self-contained breathing apparatus.

6. Accidental Release Measures

Steps to be taken in case of spill or release

Dike and contain with inert material. Transfer spilled material to containers. Avoid breathing vapors. Ventilate area. Use non-sparking tools.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of the MSDS provide information regarding certain federal and state requirements.

7. Handling and Storage

Handling - Avoid contact with skin and eyes. Wash thoroughly after handling. Use this product with adequate ventilation.

Storage - Keep away from heat and open flames.

8. Exposure Controls and Personal Protection

Eye Protection - Use proper protection – safety glasses as a minimum.

Skin Protection - Impervious gloves are suggested.

Ventilation - Local exhaust ventilation is recommended to maintain vapor level below TLV.

Respiratory Protection - If engineering controls do not maintain airborne concentrations of hazardous ingredients below TLV, then a NIOSH/MSHA approved organic vapor respirator should be used. Not required under normal usage and adequate ventilation.

Other Protective Equipment - Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

Hygienic Practices - Eye wash and safety shower should be available. Use under well ventilated conditions. Personnel should wash thoroughly after handling product. Always wash-up before eating, smoking, or using toilet facilities. Do not breathe vapor, do not contact eyes, skin and clothing.

9. Physical and Chemical Properties

Color/Appearance	Black
Odor	Solvent Odor
Boiling/Cond. Point	160°F
Melting/Freezing Point	Not applicable
Solubility	Insoluble in water
Vapor Density	<1 (air=1)
Vapor Pressure	110 mg Hg

10. Stability and Reactivity

Chemical Stability	Stable
Hazardous Polymerization	Will not occur
Material to Avoid / Incompatibilities	Keep away from strong oxidizing agents.

11. Toxicological Information

Carcinogenicity	This product is not known to be a carcinogen.
Sensitizer	This product is not known to be a sensitizer.
Mutagenicity	This product is not known to be a mutagen.
Reproductive Toxin	This product is not known to be a reproductive toxin.
Teratogenicity	This product is not known to be a teratogen.

12. Ecological Information

Environmental Fate and Distribution	Complete information is not yet available
Environmental Effects	Complete information is not yet available
Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available

13. Disposal Considerations

Waste Disposal Method – We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This material if discarded may be hazardous under US EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

14. Transportation Information

DOT Road Shipment Information ORM-D Exempt for Ground Shipment

DOT Classification: Class 3 (Flammable Liquids)
Proper Shipping Name: Methyl Ethyl Ketone
UN/NA Number: UN1993

15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200

TSCA Status – All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA Title III Section 302 Extreme Hazardous Substances – None

SARA Title III Section 304 CERCLA Hazardous Substances – Methyl Ethyl Ketone (78-93-3), Xylene (1330-20-7)

SARA Title III Section 313 Toxic Chemicals – Methyl Ethyl Ketone (78-93-3), Xylene (1330-20-7)

California Proposition 65 This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None Known

New Jersey - Methyl Ethyl Ketone (78-93-3), Xylene (1330-20-7)

Pennsylvania - Methyl Ethyl Ketone (78-93-3), Xylene (1330-20-7)

16. Other Information

Disclaimer – The Data contained herein is based upon information that Superco Specialty products believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained by the use thereof.