

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 1139

IDENTITY: HIGH GLOSS

Revision Date: 01/05/2006

Section I

Manufacturer's Name: SUPERCO SPECIALTY PRODUCTS

Address: 25041 ANZA DRIVE

VALENCIA

State: CA Zip Code: 91355

Telephone Numbers:

Emergency:

800/255-3924

Information:

661/775-9-8877

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
GLYCOL ETHER DPM	34590-94-8	ND	ND		---
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	---
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 212 + Specific Gravity (water=1) 0.99
Vapor Pressure(mm Hg) 46PSI Melting Point: N/A
Vapor Density(AIR=1) N/A Evaporation Rate: <1
Solubility in Water: 100% (Butyl Acetate=1)
Appearance and Odor: WHITE FOAM, MILD ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used):NONE Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS
WHEN INDICATED

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING

Section V: REACTIVITY DATA

PRODUCT NUMBER: 1139

=====
Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120 F

Incompatibility (Materials to Avoid): NONE

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

=====
Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards(Acute and Chronic):
INHALATION: EXCESSIVE INHALATION MAY CAUSE SLIGHT DIZZINESS. EYES: IRRITA-
TION AND REDDENING. SKIN: SLIGHT IRRITATION.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES:
FLUSH WITH RUNNING WATER FOR 15 MINUTES AND CONTACT PHYSICIAN. SKIN: WASH
THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, CONTACT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====
Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG
OR USE AN ABSORBENT CLAY MATERIAL OR TOWEL. DISPOSE OF IN ACCORDANCE WITH
FEDERAL, STATE AND LOCAL GUIDELINES

Waste Disposal Method: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT
REUSE EMPTY CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR
HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE
BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

=====
Respiratory Protection: N/A
Ventilation: Local Exhaust:N/A
Mechanical: N/A Special: N/A
Other: N/A

Protective Gloves:N/A

Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment:

N/A

Work/Hygienic Practices:

N/A