

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 1069

IDENTITY: HURRICANE-A 20A

Revision Date: 02/11/2009

Section I

Manufacturer's Name: CNS INDUSTRIES \*\*\*  
Address: DBA/SUPERCO  
25041 ANZA DRIVE  
VALENCIA  
State: CA Zip Code:91355

Telephone Numbers:  
Emergency:  
800/255-3924  
Information:  
800/320-0102

HMS CODES: REACTIVITY: 1 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
2-BUTOXY ETHANOL	* 111-76-2	25 PPM	25 PPM	N/A	___
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	___

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN \* SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	212 +	Specific Gravity (water=1)	1.00
Vapor Pressure(mm Hg)	17.5	Melting Point:	N/A
Vapor Density(AIR=1)	N/A	Evaporation Rate:	<1
Solubility in Water:	100%	(Butyl Acetate=1)	

Appearance and Odor: WHITE FOAM, MILD LEMON/AMMONIA ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used):NONE Flammable Limits: LEL:N/A UEL: N/A  
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER  
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS WHEN INDICATED

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE.  
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING

Section V: REACTIVITY DATA

PRODUCT NUMBER: 1069

Stability: Unstable: Conditions to avoid:  
Stable: X TEMPERATURES ABOVE 120 F  
Incompatibility (Materials to Avoid): NONE

Hazardous Decomposition or Byproducts: OXIDES OF CARBON

Hazardous Polymerization: May Occur: Will Not Occur: X  
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES  
Health Hazards(Acute and Chronic):  
INHALATION: EXCESSIVE INHALATION MAY CAUSE SLIGHT DIZZINESS. EYES: IRRITATION AND REDDENING. SKIN: SLIGHT IRRITATION

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO  
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES:  
FLUSH WITH RUNNING WATER FOR 15 MINUTES. SKIN: WASH COMPLETELY WITH RUNNING WATER. IF IRRITATION PERSISTS, CONSULT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG  
OR USE AN ABSORBENT CLAY MATERIAL OR TOWEL. DISPOSE OF IN ACCORDANCE WITH  
FEDERAL, STATE AND LOCAL GUIDELINES

Waste Disposal Method: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT  
REUSE EMPTY CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR  
HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE  
BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: N/A  
Ventilation: Local Exhaust:N/A  
Mechanical: N/A Special: N/A  
Other: N/A  
Protective Gloves:N/A  
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.  
Other Protective Clothing or Equipment:  
N/A  
Work/Hygienic Practices:  
N/A