MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 1105
IDENTITY: REVIVE-A 20A Revision Date: 03/04/2004

Section I

Manufacturer's Name: CNS INDUSTRIES ***
Address: DBA/SUPERCO
25041 ANZA DRIVE
VALENCIA
State: CA Zip Code: 91355

Telephone Numbers:
Emergency:
800/255-3924
Information:
800/320-0102

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 2 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
ISOPARAFINIC HYDROCARBON	64742-47-8	400 PPM	400 PPM		___
PETROLEUM DISTILLATES	64742-54-7	5 MG/M3	10 MG/M3	N/A	___
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	___

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	388	Specific Gravity (water=1)	0.82
Vapor Pressure(mm Hg)	.5	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate: (Butyl Acetate=1)	.2
Solubility in Water:	0%		

Appearance and Odor: CLEAR SPRAY/LEMON SCENT

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): 130 F TCC Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS WHEN INDICATED

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 1105

Stability: Unstable: Conditions to avoid:
Stable: X CONDITIONS ABOVE 120 F
Incompatability (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion:YES
Health Hazards(Acute and Chronic):
INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY LEAD TO UNCONSCIOUSNESS. EYES: IRRITATION, REDDENING. SKIN: MAY CAUSE LOCALIZED DRYNESS IF OVER EXPOSED.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. SKIN: IN CASE OF CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. EYES: FLUSH THOROUGHLY AND SEE DOCTOR. CONTACT PHYSICIAN IF IRRITATION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL. DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Waste Disposal Method: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAMES. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.
Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: N/A
Ventilation: Local Exhaust:N/A
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves:N/A
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHEN USING CHEMICAL PRODUCTS
Other Protective Clothing or Equipment:
N/A

Work/Hygienic Practices:
WASH HANDS AFTER USE