

MATERIAL SAFETY DATA SHEET

WHMIS, SAFE HANDLING, AND DISPOSAL INFORMATION

ISSUE DATE: 10/14/2005 PRODUCT NAME: **SAFE STRIP B #2021** HAZ CLASS: IRR
SUPERSEDES: 10/05/2005 PRODUCT TYPE: Earth Friendly Industrial Paint Stripper

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

SUPERCO SPECIALTY PRODUCTS

25041 ANZA DRIVE
VALENCIA, CA 91355
PREPARED BY: Tech Service (jnj)

TELEPHONE: (661)775-8877
EMERGENCY TELEPHONE: (800)255-3924
FAX: (661)775-8884

TRANSPORTATION AND CHEMICAL EMERGENCY: CHEMTEL - 800-255-3924

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

<u>HAZARDOUS INGREDIENTS</u>	<u>% WT</u>	<u>CAS #</u>	<u>LD₅₀(Route, Species)</u>	<u>LC₅₀(Species)</u>
Benzyl Alcohol	30-40	100-51-6	1230 mg/kg (oral, rat)	N/AV
Petroleum Distillate, Naphthenic	5-<10	68477-31-6	N/AV	N/AV
Glycolic Acid	1-<5	79-14-1	1938 mg/kg (oral, rat)	3.6 mg/L/ 4hr (rat)

SECTION 3 – HAZARDS IDENTIFICATION

ROUTES OF ENTRY: (X)Skin Contact, (X)Skin Absorption, (X)Eye Contact, (X)Inhalation, (X)Ingestion

TARGET ORGANS: Eyes, skin, and mucous membranes.

EMERGENCY OVERVIEW: Moderate eye, skin, and respiratory irritant.

WHMIS SYMBOLS:



SPECIAL NOTE: MSDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under recommended conditions of use so long as prescribed safety precautions are practiced. See product bulletin for use instructions.

POTENTIAL HEALTH EFFECTS: Chronic contact may lead to inflammation or dermatitis.

SECTION 4 - FIRST AID MEASURES

SKIN CONTACT: Immediately flush contaminated skin with plenty of water. Get medical attention for burns.

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower lids. Get immediate medical attention.

INHALATION: Move exposed person to fresh air. If irritation persists, get medical immediate attention.

INGESTION: If this product is swallowed, DO NOT INDUCE VOMITING. If victim is conscious give plenty of water to drink. Get medical attention at once.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABILITY: Non-flammable under normal use conditions. CONDITIONS: Must be heated above 100°C.

EXTINGUISHING MEDIA: (X)Water, (X)Alcohol Foam, (X)CO₂, (X)Dry Chemical, (X)Water Fog

FLASH POINT (°C): 105°C (PMCC)

FLAMMABLE LIMITS, LEL: N/AV UEL: N/AV%

AUTO IGNITION TEMPERATURE: >400°C

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Toxic gases may form when this product comes in contact with extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained positive pressure breathing apparatus. Keep containers cool with water spray.

HAZARDOUS COMBUSTION PRODUCTS: Carbon oxides and dark smoke may be created by combustion.

NFPA® "DIAMOND" RATING: Health(2), Flammability(1), Reactivity(0), Special Hazards(None)

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPECIAL LEAK AND SPILL PROCEDURES: Observe safety procedures in SECTION 7 & 8 during clean up. Spilled product may be slippery to walk on. Ventilate the area with fans. **SMALL SPILL:** apply an inert absorbent material on the spill, pick up, and place in a designated waste container. Do not return spilled stripper to the original container. **LARGE SPILL:** dike off to prevent sewer entry or ground runoff, and reclaim for reuse or disposal. Place only in well vented plastic containers. For remaining residues, if allowed thoroughly rinse off spill area with water, otherwise see **SMALL SPILL** instructions. The ideal choice for a waste container is an open top dense polyethylene or polypropylene plastic.

SECTION 7 – HANDLING AND STORAGE

HANDLING PROCEDURES AND EQUIPMENT: Prior to use, all organic solvents, and products containing heavy metals, such as chromate conversion compounds must be removed from the area. Wear protective gear (see Section 8). **DO NOT** use in enclosed space. Open containers slowly to relieve pressure build up. Keep product out of eyes. Avoid contact with skin. Keep away from food and food products. Keep out of the reach of children. Do not immediately seal waste containers; spent material is packaged in vented, plastic containers.

STORAGE REQUIREMENTS: Protect container against physical damage by storing in a designated, cool, dry, ventilated area away from foodstuffs. Do not store above 120°F (48°C).

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

<u>HAZARDOUS INGREDIENT</u>	<u>OSHA PEL/STEL</u>	<u>ACGIH TLV/STEL</u>	<u>OTHER (Specify)</u>
Benzyl Alcohol	N/AV	N/AV	IRR, CBL
Petroleum Distillate, Naphthenic	N/AV	N/AV	IRR, CBL
Glycolic Acid	N/AV	N/AV	COR

HMIS III® CODES: Health (2), Flammability (1), Physical Hazard (1), Chronic Hazard: No

ENGINEERING CONTROLS: No extra measures are needed if TLV is not exceeded. Use local exhaust ventilation (explosion proof) to keep vapor concentration (TLV) below exposure limits. Maintain a safety shower and eye wash station near the work area.

PERSONAL PROTECT EQUIP: (X)Gloves, (X)Respirator, (X)Eyes, (X)Footwear, (X)Clothing, ()Other (Specify)

RESPIRATORY PROTECTION: Use engineering controls to reduce emission levels. If exposure limits for hydrogen peroxide are exceeded, wear an approved NIOSH respirator of either an organic/acidic mist or a full-face air supplied type.

PROTECTIVE CLOTHING: Wear Neoprene® rubber gloves, boots, and apron. Wear a protective rain suit for spray application use.

EYE PROTECTION: Wear tight fitting goggles and face shield, for material transfer and application.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Orange, viscous emulsion

ODOR: Mild acrid odor

ODOR THRESHOLD: 10 ppm

SPECIFIC GRAVITY: 1.0

VAPOR DENSITY (Air=1): >1

VAPOR PRESSURE (mmHG): 15.5 mmHg_{20°C}

EVAPORATION RATE (WATER=1): 20

BOILING POINT (°C): 100-205°C (decomposes)

MELTING POINT (°C): <0°C

PH (CONC): 2-3 PH (10%): N/AP

COEFFICIENT WATER/OIL DISTRIBUTION: <1

SOLUBILITY IN WATER: 57.7%

VOC (EPA Method 24): 397 g/L and 10 g/L (alternate)

SECTION 10 – STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable

INCOMPATIBILITY (AVOID): Avoid contact with strong mineral acids, strong oxidizers, or strong alkalis

REACTIVITY/CONDITIONS: Decomposes when heated above 70-80°C.

CONDITIONS TO AVOID: Do not expose to open flame and sparks.

HAZARDOUS DECOMPOSITION PRODUCTS: May decompose to carbon monoxide, carbon dioxide, or other organic products.

SECTION 11 - TOXICOLOGICAL INFORMATION

ACUTE EXPOSURE EFFECTS: Vapors and mists are irritating to eyes and respiratory system. Eye and skin contact produces stinging and a white wound that clears in a short period of time. Prolonged eye or skin contact may cause more serious burns. Ingestion may cause gastrointestinal complications.

CHRONIC EXPOSURE EFFECTS: Repeated contact (over period of a few weeks) may produce dermatitis.

IRRITANCY OF PRODUCT: Moderate; SKIN AND RESPIRATORY SENSITIZATION: Not likely to occur.

GENETIC TOXICITY: This product contains no known ingredients listed by OSHA, ACGIH, IARC, NTP or Health Canada, which are considered carcinogenic, teratogenic, nor other known ingredients that would interfere with reproduction.

SECTION 12 - ECOLOGICAL INFORMATION

BIODEGRADABILITY (40 CFR 796.3100): Chemical Oxygen Demand (COD): 1466 g/L (theoretical)

AQUATIC TOXICITY (EPA-600-4-91-002): Not determined.

OTHER: Entry of large quantities of product in waterways may be toxic to marine animals.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Do not put product in metal containers for disposal. Consult your local, state (provincial), and federal agencies for proper disposal method in your area. Do not contaminate water supply when disposing of wastes or containers.

SECTION 14 – TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Not Regulated

TDG/DOT HAZARD CLASS: N/AP

TDG/DOT PACKING GROUP: N/AP

PIN: N/AP

TDG/DOT ID NUMBER : N/AP

TDG/DOT LABEL/PLACARD: N/AP

SECTION 15 – REGULATORY INFORMATION

WHMIS CLASSIFICATION: D2B

RCRA HAZARDOUS WASTE NOS: None;

SARA 313 TOXIC CHEMICALS: None

TSCA: All components of this product are registered under regulations of the Toxic Substances Control Act.

RQ CERCLA 40 CFR PART 302: None

California Proposition 65 Chemicals: None

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations (CPR)*. The MSDS contains all of the information required by the CPR.

SECTION 16 – OTHER INFORMATION

TRADE NAME AND SYNONYMS: None

SPECIFICATION: None

NSN: N/AP, CAGE CODE: 55208

HMRA ID: N/AV

CONTRACT NUMBER: N/AP

Revision summary: Corrected hygiene information in Section 5. Added additional regulatory information to Sections 9 (bef).

OTHER: Thank you for your interest in and use of Superco products. We are pleased to be of service to you by supplying this Material Safety Data Sheet for your files. Superco is concerned for your health and safety. Our products can be used safely with proper protective equipment and with proper handling practices consistent with label instructions and the MSDS. Before using any product, be sure to read the complete label and the Material Safety Data Sheet.

As a further word of caution, Superco advises that serious accidents have resulted from the misuse of “emptied” containers, which retain residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such container to heat flame, sparks, or other sources of ignition; they may explode or develop harmful vapors and possibly cause injury or death. Empty containers must be cleaned by triple rinsing with water or an appropriate solvent. Empty containers must be sent to a drum reconditioner before reuse.

This MSDS also complies with information required by OSHA 29 CFR 1910.1200, and with additional information requirements stated in FED-STD-313D. It was formatted as outlined by the ANSI Standardized MSDS 16 Part Format Z400.1-1998 and by the Canada’s “Controlled Product Regulations”, Section 12.

DISCLAIMER: All statements, technical information and recommendations contained herein are based on available scientific tests or data, which we believe to be reliable. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. Superco Specialty Products, Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of our products, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the product label and Material Safety Data Sheet. Revisions: added COD to section 12.