

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 06/23/2010

Reviewed on 06/23/2010

1 Identification of substance

Trade name: SUPERCOAT GRAY PRIMER
Product codes: # 1431
Manufactured For: SUPERCO SPECIALTY PRODUCTS
25041 Anza Drive
Valencia, CA 91355
(661)775-8877, www.supercoproducts.com

Emergency information: CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*

2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with non-hazardous additions.

Dangerous components:

67-64-1	Acetone	39.08%
74-98-6	propane	15.74%
67-63-0	isopropyl alcohol	10.9%
106-97-8	n-butane	9.25%
77-90-7	Acetyl Tributyl Citrate	3.15%
2807-30-9	Glycol Ether EP	2.86%
557-05-1	zinc distearate, pure	2.0%
64742-47-8	Mineral Spirits	1.27%
108-65-6	PM acetate	1.06%

3 Hazards identification

Hazard description:



Irritant

Extremely flammable

Physical dangers:

Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.

Has narcotizing effect.

Extremely flammable.

Irritating to eyes.

Vapors may cause drowsiness and dizziness

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (0 - 4):

Health = 1

Fire = 4

Reactivity = 3

HMIS-ratings (0 - 4):

Health= 1

Fire= 4

Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents: CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

Protective equipment: No special measures required.

6 Accidental release measures

Personal safety: Wear protective equipment. Keep unprotected persons away.

Environmental safety: Do not allow product to reach sewage systems or ground water.

Clean-up/collection: Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL 2400 mg/m³, 1000 ppm
REL 590 mg/m³, 250 ppm
TLV Short-term value: 1782 mg/m³, 750 ppm
Long-term value: 1188 mg/m³, 500 ppm
BEI

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm
REL 1800 mg/m³, 1000 ppm
TLV Varies mg/m³, 1000 ppm

67-63-0 isopropyl alcohol

PEL 980 mg/m³, 400 ppm
REL Short-term value: 1225 mg/m³, 500 ppm
Long-term value: 980 mg/m³, 400 ppm
TLV Short-term value: 984 mg/m³, 400 ppm
Long-term value: 492 mg/m³, 200 ppm
BEI

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
TLV Varies mg/m³, 1000 ppm

557-05-1 zinc distearate, pure

PEL 15* 5** mg/m³
*total dust **respirable fraction
REL 15* 5** mg/m³
*total dust **respirable fraction
TLV 10 mg/m³

108-65-6 PM acetate

WEEL 50 ppm

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties:

General Information:

Odor:	Aromatic
Boiling point:	-44°C (-47°F)
Flash point:	-19°C (-2°F)
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	12.0 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density at 20°C (68°F):	0.78 g/cm ³
Specific Gravity:	Between 0.77 and 0.85 (Water equals 1.00)
VOC content:	538.6 g/l / 4.50 lb/gal
VOC content (less exempt solvents):	42.3 %
MIR Value:	0.60
Solids content:	15.6 %

10 Stability and reactivity:

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Materials to be avoided:

Hazardous Reactions: No dangerous reactions known.

11 Toxicological information:

Skin effects: No irritant effect.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Other information:

Product does not contain CFC's. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.

Aquatic toxicity: Hazardous for water, do not empty into drains.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact.

Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information:

Hazard class: 2.1

Identification number: N/A

Label: 2.1

ADR/RID/TDG class: 2.5F Gases

UN-Number: 1950

IMDG Class: 2.1

Packaging group: II

EMS Number: F-D,S-U

Marine pollutant: No

ICAO/IATA Class: 2.1

Proper shipping name: Aerosols, Flammable Consumer Commodity ORM-D

15 Regulations

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

67-63-0 isopropyl alcohol

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

1333-86-4 Carbon black

CANADIAN

ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

WHMIS Symbols for

Canada: A - Compressed gas

D2B - Toxic material causing other toxic effects

EPA: A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

I: 'Data are inadequate for an assessment of human carcinogeni potential.'

II: 'Inadequate information to assess carcinogenic potential.'

67-64-1 Acetone I

557-05-1 zinc distearate, pure II

IARC: Group 2A: The ingredient is probably carcinogenic to humans.

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

67-63-0 isopropyl alcohol 3

13463-67-7 titanium dioxide 2B

ACGIH: A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

67-64-1 Acetone A4
67-63-0 isopropyl alcohol A4
13463-67-7 titanium dioxide A4

NIOSH:

13463-67-7 titanium dioxide
1333-86-4 Carbon black

Risk phrases: Extremely flammable. Irritating to eyes. Vapors may cause drowsiness and dizziness

Safety phrases: Keep out of the reach of children. Do not breathe gas/fumes/vapour/spray. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

PP: Severe Marine Pollutant

P: Marine Pollutant

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

ISO: International Organization for Standardization

EPA: Environmental Protection Agency

IARC: International Agency for the Research of Cancer

NIOSH: National Institute for Occupational Safety and Health

TSCA: Toxic Substances Control Act

CPSC: Consumer Product Safety Commission